

METHOD AND APPARATUS FOR IMPROVING THE DYNAMIC
RANGE OF LASER DETECTED ULTRASONIC IN
ATTENUATIVE MATERIALS

5 TECHNICAL FIELD OF THE INVENTION

 The present invention relates generally to a field of optical information
processing and more particularly to a method and system for detecting ultrasonic
displacements in a material under test utilizing a time-varying output pulse of a
laser beam.

10

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000

BACKGROUND OF THE INVENTION

In recent years, the use of advanced composite structures has experienced tremendous growth in the aerospace, automotive, and many other commercial industries. While composite materials offer significant improvements in performance, they require strict quality control procedures in the manufacturing processes. Specifically, non-destructive evaluation ("NDE") methods are required to assess the structural integrity of composite structures, for example, to detect inclusions, de-laminations and porosities. Conventional NDE methods, however, are very slow, labor-intensive, and costly. As a result, testing procedures adversely increase the manufacturing costs associated with composite structures.

Various systems and techniques have been proposed to assess the structural integrity of composite structures. One method to generate and detect ultrasound using lasers discloses the use of a first modulated, pulsed laser beam for generating ultrasound on a work piece and a second pulsed laser beam for detecting the ultrasound. Phase modulated light from the second laser beam is then demodulated to obtain a signal representative of the ultrasonic motion at the surface of the work piece.

Another method to generate and detect ultrasound using lasers discloses the use of a laser to detect deformations of an oscillatory or transient nature on a material under test surface. The deformations on the material under test surface can be produced by an ultrasound wave or other excitation. Light from the laser is scattered by the deformations, some of which light is collected by collecting optics and transmitted via a fiber optic to a beam splitter which deflects a small portion of the collected light to a reference detector and delivers the remaining portion of the light to a confocal Fabry-Perot interferometer, which generates an output signal indicative of the deformations on the material under test surface. The reference detector measures the intensity of the scattered laser light at the input of the interferometer to generate a reference signal. A stabilization detector measures the intensity of the scattered laser light at the output of the interferometer to generate a prestabilization signal. The ratio of the reference

signal to the prestabilization signal is used to generate a final stabilization signal which drives a piezoelectric pusher inside the interferometer to adjust its resonant frequency.

5 The advanced composite structures often attenuate ultrasound within the composite materials. It would be desirable to have a system capable of expanding the dynamic range of ultrasound detection in an attenuative material such as advanced composites.

10 The above-referenced methods attempt to reduce the noise associated with the detection schemes. However, the methods disclosed do not explore expanding and improving the dynamic range of ultrasound detection in attenuative materials.

15 Therefore, there is a need has arisen for a method and system of ultrasonic laser detection that overcomes the disadvantages and deficiencies of the prior art. Namely, such a system should be able to extend the dynamic range of ultrasound detection in an attenuative material.

SUMMARY OF THE INVENTION

The present invention provides a method and system for detecting ultrasonic displacements at a remote target under test utilizing a laser beam that substantially eliminates or reduces disadvantages and problems associated with previously developed ultrasonic detection systems.

More specifically, the present invention provides a system for detecting ultrasonic displacements at a remote target with a laser beam having a time dependent pulse profile. The system and method for improving the dynamic range of laser detected ultrasonic in attenuative materials includes a seed laser light source. This laser source produces a laser which is modulated by an assembly placed in the laser beam's path. The modulated laser has a time-dependent pulse profile. Ultrasonics at the remote target further modulate, reflect and/or scatter the laser beam to produce phase-modulated light. Optics collect this phase modulated light. An interferometer coupled to the collection optics demodulates the phase-modulated light and provide an output signal representative of the ultrasonics at the remote target.

A processor may be utilized to process output signal of the interferometer to obtain data representative of the ultrasonics.

Another embodiment of the present invention involves matching the time-dependent pulse profile of the detection laser beam to the attenuative properties of the remote target. Alternatively, the time-dependent pulse profile may be varied to increase the signal strength of the detected ultrasonics.

The present invention provides an important technical advantage by extending the dynamic range of a Laser UT system. Previous systems would synchronize the generation of the ultrasonic event with the peak of the detection laser to maximize signal-noise-ratio without regard for potential dynamic range improvements based on exploiting non-uniform illumination profiles, while the present invention provides that the use of time-dependent detection laser illumination profiles can be used to both optimize signal-noise-ratio and extend the dynamic range of the Laser UT systems.

Another technical advantage of the present invention is an extended dynamic range with which to detect ultrasound in the material under test and improved signal-to-noise ratio due to the time-varying pulse profiles of the detection laser.

5 Yet another technical advantage of the present invention is the ability to use a detection laser with lower output power. This allows the use of smaller collection optics and optical scanners. Additionally, the use of a lower power detection laser reduces the total power applied to the material under test and damage of the material under test.

10 Stored energy in amplifier can be extracted in an optimum way to match the properties of the material under test.

BRIEF DESCRIPTION OF THE DRAWINGS

For a more complete understanding of the present invention and advantages thereof, reference is now made to the following descriptions taken in conjunction with the accompanying drawings in which like reference numbers
5 indicate like features and wherein:

FIGURE 1 depicts a known setup for detecting ultrasonic displacements using a detection laser beam;

FIGURE 2 illustrates shows an embodiment of the present invention using a time-dependent output pulse profile to yield an improved signal-to-noise ratio;

10 FIGURE 3A illustrates a gaussian or lorentzian time-dependent pulse profile;

FIGURE 3B illustrates a linear ramp to a gain clamped time-dependent pulse profile;

15 FIGURE 3C illustrates an exponential ramp to a gain clamped time-dependent pulse profile; and

FIGURE 4 illustrates a typical plot of frequency dependent material attenuation.

DETAILED DESCRIPTION OF THE INVENTION

Preferred embodiments of the present invention and its advantages are understood by referring to FIGURES 1 through 6 of the drawings, like numerals being used for like and corresponding parts of the various drawings.

FIGURE 1 illustrates a detection system 100 for detecting ultrasonic displacements 102 at remote target 104. Detection system 100 utilizes a detection laser source 106 to generate a laser beam 108. Detection laser source 106 may incorporate a multi-pass optical amplifier 110, driven by pump source drive electronics 109 to generate laser beam 108 with a power P_0 . Ultrasonic displacements 102 at remote target 104 modulate, scatter and reflect detection laser beam 108. When detection laser beam 108 interacts with the ultrasonic waves or displacements 102 present at remote target 104, detection laser beam 108 is reflected or scattered as phase-modulated light 112. Phase-modulated light 112 is reflected and scattered in all directions as shown by arrows 114. However, some of the phase-modulated light 112 is captured by collection optics 116. Collection optics 116 direct phase-modulated light 112 via fiber optic 118 into interferometer 120. Interferometer 120 demodulates the phase-modulated light and directs an output into detector 122 which generates an analog signal for processing.

Scattering of the laser beam by the material under test includes all reactions between laser beam 108 and the material under test where laser beam 108 is redirected without otherwise altering the laser beam; furthermore scattering a laser beam by the material under test includes all reactions between the phase modulated light and the material under test with the exception of absorption of the first pulsed laser beam.

Collection optics 116 has an aperture size of ϕ and is spaced a distance D from remote target 104. The power of the collected, phase-modulated light as measured at the output of the collector is P_c . The power of the collected, phase-modulated light at the input of the interferometer is substantially P_c since there is very little transmission loss associated with fiber optic 118. Because the loss in

interferometer is minimal, the power of the input signal to the detector (P_{DET}) is substantially the same as P_o .

The signal-to-noise ratio of detector 122 is directly proportional to the square root of the input power:

$$SNR \propto \sqrt{P_{DET}} \quad \text{eqn (1)}$$

The above formulas suggest that the SNR can be improved by increasing P_o , or ϕ , or by decreasing D . Increasing the ratio of ϕ/D decreases the depth of field of detection system 100, which is undesirable because a decreased depth of field is less flexible.

Alternatively, P_o can be increased. One approach to increase the output of detection laser 106 is to use a shorter pulse width. The pulse of detection laser beam 108, however, must be of a sufficient width to permit detection of ultrasonic displacements, and therefore, decreasing its pulse duration degrades its ability to detect such displacements. A second approach is to amplify the detection laser using a multiple pass optical amplifier. However, the gain of a conventional optical amplifier is dependent upon the power of the input signal.

Where the P_{DET} is given by eqn (2):

$$P_{DET} = \frac{P_o}{4} \left(\frac{\phi}{D} \right)^2 (1-A) \cdot \cos \sigma \cdot \eta \quad \Leftarrow \text{for a diffuse surface}$$

Where P_o = incident power

A = absorption

σ = incident angle

η = efficiency (mirror losses, fiber losses, etc.)

FIGURE 2 illustrates a setup for generating and detecting ultrasonic displacements using a detection laser beam similar to that of FIGURE 1.

Detection system 200 utilizes a detection laser 130 to detect ultrasonic displacements 102 on a remote target 104. Detection laser 130 may incorporate an electro optic phase modulator 132 to modulate the laser based on time varying drive voltage. Optical isolator 134 and beam dump 136 to prevent optical feedback into modulator 132. Optical amplifier 138 amplifies the laser beam to produce laser beam 140 with a power $P_{(t)}$. This laser beam 140 can have a time-

dependent pulse profile $P_{(t)}$, this pulse profile can be optimized as to improve the signal strength. This time-dependent pulse profile can be optimized to substantially match the attenuation characteristics of remote target 104.

Alternatively, a time-dependent pulse profile can be used which does not match the attenuation characteristics of remote target 104 but does provide sufficient variation in the intensity of the pulse profile to alter the dynamic range of the ultrasonic detection process. FIGURES 3A through 3C illustrate potential pulse shapes, including a gaussian or lorentzian pulse shape as shown in FIGURE 3A; a linear ramp/gain clamping pulse shape as shown in FIGURE 3B; and an exponential pulse shape as shown in FIGURE 3C. The present invention need not be limited to the time-dependent pulse profiles described in FIGURES 3A through 3C. Rather, advantageous pulse profiles may be taken such that the signal strength actually increases during the duration of the detection pulse.

The present invention provides a system for detecting ultrasonic displacements at a remote target. The ultrasonic displacements 102 at remote target 104 modulate, scatter and reflect detection laser beam 140, represented by arrows 142 directed away from the remote target 104. When detection laser beam 140 interacts with ultrasonic waves 102, detection laser beam 140 is reflected and/or scattered as phase-modulated light 142. This phase-modulated light contains information representative of the ultrasonic displacements 112 at remote target 104.

Ultrasonic material displacements 102 are a function of both time and attenuation of the material from which remote target 104 is constructed. This function is shown below in Equation 1.

$$U_{(t)} = U_0 e^{-\alpha_{(f)} t} \quad (\text{EQN 1})$$

Where $\alpha_{(f)}$ is the frequency dependent material attenuation as shown in FIGURE

4. The measured signal at the detector is given by Equation 2, as follows:

$$S_{(t)} = K \cdot P_{(t)} \cdot U_{(t)} \quad (\text{EQN 2})$$

Where K is a constant, $P_{(t)}$ is the detection laser power and $U_{(t)}$ is the ultrasonic displacements defined in Equation 1. Over a small frequency range (Δf), the

frequency-dependent material attenuation as shown in FIGURE 4 can be approximated by a constant:

$$\alpha_{(t)} \approx \alpha_0$$

Further, the time-dependent pulse profile $P_{(t)}$ can be adjusted such that the pulse profile of the laser 140 substantially matches the attenuation characteristics of the material under test, as shown by the below approximation: $P_{(t)} \approx e^{+\alpha_0 t}$. These approximations associated with the exponential pulse profile of FIGURE 3C, yield a measured signal described by Equation 3 below:

$$S_{(t)} = K \cdot U_0 \cdot e^{+\alpha_0 t} \cdot e^{-\alpha_0 t} = K \cdot U_0 \quad (\text{EQN 3})$$

Here, the pulse profile, $P_{(t)}$, has been made to exactly match the attenuation loss, yielding a constant measured signal strength over time.

Similarly, the pulse profiles provided in FIGURES 3A and 3B allow for an improved signal strength response utilizing a different $P_{(t)}$ function.

More specifically, the present invention provides a system for detecting ultrasonic displacements at a remote target with a laser beam having a time dependent pulse profile. The system and method for improving the dynamic range of laser detected ultrasonic in attenuative materials includes a seed laser light source. This laser source produces a laser which is modulated by an assembly placed in the laser beam's path. The modulated laser has a time-dependent pulse profile. Ultrasonics at the remote target further modulate, reflect and/or scatter the laser beam to produce phase-modulated light. Optics collect this phase modulated light. An interferometer is coupled to the collection optics to demodulate the phase-modulated light and provide an output signal representative of the ultrasonics at the remote target.

A processor may be utilized to process the one output signal of the interferometer to obtain data representative of the ultrasonics.

Another embodiment of the present invention involves matching the time-dependent pulse profile of the detection laser beam to the attenuative properties of the remote target. Alternatively, the time-dependent pulse profile may be varied to increase the signal strength of the detected ultrasonics.

The present invention provides an important technical advantage by extending the dynamic range of a Laser UT system. Previous systems would synchronize the generation of the ultrasonic event with the peak of the detection laser to maximize signal-noise-ratio without regard for potential dynamic range improvements based on exploiting non-uniform illumination profiles, while the present invention provides that the use of time-dependent detection laser illumination profiles can be used to both optimize signal-noise-ratio and extend the dynamic range of the Laser UT systems.

Another technical advantage of the present invention is an extended dynamic range of the system to detect ultrasound in the material under test and improved signal-to-noise ratio for the system due to the time-varying pulse profiles of the detection laser. The time-varying signal can be matched to the attenuative properties of the material, thus optimizing the signal-to-noise ratio of the output signal provided by the detection laser.

Yet another technical advantage of the present invention is the ability to use a detection laser with lower output power allowing the use of smaller collection optics and optical scanners. Additionally, the use of a lower power detection laser reduces the total power applied to the material under test and damage of the material under test. This reduced power requirement is due to the improved signal-to-noise ratio and dynamic range achieved by the application of the time-varying laser pulse.

Although the present invention has been particularly shown and described in detail, it should be understood that various changes, substitutions and alterations can be made hereto without departing from the spirit and scope of the invention as defined in the appended claims.